

PPSTM **Pollution Protection Systems Mumbai Pvt. Ltd.**
 Gas Detection & Monitoring Systems

Regd. Off.: 10, Chandravijay, L.T. Road,
 Mulund (East), Mumbai - 400 081. INDIA
 Tel.: 91-22-2564 7527
 E-mail : polutn.purvi@vsnl.com
 Web Site : www.ppsmumbai.com


 ISO 9001-2000 CERTIFIED

Works.: 226, Devendra Industrial Estate, Lokmanya Nagar,
 Pada No. 2, Yashodhan Nagar, Thane (W) - 400 606.
 Telefax.: 91-22- 2585 6570 / 2588 3328
 E-mail : pptl@bom5.vsnl.net.in
 ● CCE APPROVED ● BIS APPROVED

Data Sheet of gaZguard Ox.

APPROVALS:

- Tested for Intrinsically safe as per **IS 5780-2002{IEC-60079-11(1999)}**
- Tested for Performance as per **IS 9000 (ERTL WEST)**
- Approved for **EEx ia IIC T4/T6**
- BIS Certificate No: - **CM / L – 7449687** as per **IS: 5780**
- CCE Approval No: -**A/P/HQ/MH/104/518(P55545)**



PPS Make Portable Oxygen Indicator

TECHNICAL SPECIFICATION:

Dimension	:	130mm x 67mm (4.5" x 2.6" x 1.6")
Weight	:	450 gms. (With Batteries)
Accessories	:	Standard: - Carrying Case Batt. Charger Optional: - Aspirator adaptor
Measurement Range	:	0 – 25% vol. or 0 – 100% vol
Display	:	Liquid Crystal Display (LCD)
Standard Alarm Levels	:	LO – 19.5% HI – 22.5%
Optional Alarm Levels	:	As per specification
Alarm Indication	:	Pulsating / Continuous red LED with audible, 90 db at 1 Meter
Battery	:	Standard: Rechargeable 4 x AA cells Optional: Disposable
Battery Life	:	12 – 15 hrs. Continuous
Oper. Temperature	:	-10 deg C to 50 deg C. (14 deg F to 122 deg F)
Humidity	:	0 – 95% RH Non - Condensing
Resolution	:	0.1%
Response Time	:	T95 < 15 Sec.
Setting	:	Zero/ Span accessible from outside
Sensor Type	:	Electrochemical
Sensor Life	:	2 to 3 years (in fresh air)