





SIGNALINE

Signaline CB200W Water Detection Panel



Signaline CB200W Water Detection Panel



For further information and specifications for the Signaline WDM-KM Control Module and Signaline WD Water Detection Cable, please refer to their data sheets.

Function	CB200W 1 & 2 zone	CB200W 4 Zone	CB200W 8 Zone
Mains Supply	230 Vac	230 Vac	230 Vac
Auxiliary 24Vdc output	250mA	250mA	250mA
Max. Batt. Charger Output	500mA @ 27.5V dc	500mA @ 27.5V dc	500mA @ 27.5V dc
Back up battery (sealed lead acid)	2 x 12 Vdc 2.1AH	2 x 12 Vdc 2.1AH	2 x 12 Vdc 2.1AH
Alarm Sounder Circuits (24Vdc)	2 x 250mA each	4 x 500mA each	4 x 500mA each
Common alarm output no/nc contact	1A, 30Vdc max	1A, 30Vdc max	1A, 30Vdc max
Common fault output no/nc contact	1A, 30Vdc max	1A, 30Vdc max	1A, 30Vdc max
Max. Field Equipment Load	800mA	800mA	800mA
Repeater Panel Option	Yes	Yes	Yes
Panel Dimensions mm (W x H x D)	313 x 245 x 66	313 x 245 x 66	313 x 245 x 66
Weight (excluding batteries)	2.3 Kg	2.3 Kg	2.4 Kg

LGM PRODUCTS LTD
UNIT 15 RIVERSIDE INDUSTRIAL PARK
FARNHAM
SURREY GU9 7UG
UNITED KINGDOM

TEL +44 (0) 1252 725257
FAX +44 (0) 1252 727627
E-mail sales@Lgmproducts.com
www.signaline.com